



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: BP192V12-3U

BP192V12-3U - External Battery Pack for UPS System

Highlights

- Extends runtime of compatible Tripp Lite UPS Systems with 192VDC external battery connection
- Provides daisy-chain capability
- Simple installation; 3U rackmount, tower or stack adaptable
- 2-year warranty



Description

Tripp Lite's BP192V12-3U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite UPS systems. Multi-use form factor supports configuration in rackmount or stacking applications using only 3 rack spaces (3U). Upright tower configuration supported with optional 2-9USTAND accessory. Includes heavy-gauge cabling with high-current DC connectors for simple installation. Additional output connector allows multiple BP192V12-3U battery packs to be daisy-chained to the UPS for even longer extended run operation.

COMPATIBLE UPS SYSTEMS - SU5000RT4U, SU6000RT4U, SU8000RT4U, and other Tripp Lite UPS systems that specify the use of this battery pack.

Applications

- Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Additional battery packs may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

Package Includes

- BP192V12-3U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Supports upright tower installation with optional 2-9USTAND accessory (holds 3 battery packs in tower configuration)
- Set of two input/output connectors allows multiple BP192V12-3U battery packs to be daisy-chained to the UPS for even longer extended run operation
- Includes heavy-gauge cabling with high-current DC connectors for simple installation
- 2-year warranty

Specifications

OUTPUT	
Overload protection	50A DC output fuse
INPUT	
Input cord length	36 in./9m, 8 AWG, 3 conductor
BATTERY	
Expandable battery runtime	Includes a second input/output connector to daisy-chain multiple battery packs
Connects to UPS via	Detachable cable with UPS specific DC connector (90 cm length, 8 gauge)
DC system voltage	192VDC
Typical battery lifespan	4-6 years typical (North America)
PHYSICAL	
Shipping weight (lbs)	211.25
Shipping weight (kg)	95.9
Shipping Dimensions (HWD/in)	11.25 x 31.5 x 23
Shipping Dimensions (HWD/cm)	28.6 x 80 x 58.4
Unit weight (lbs)	174
Unit weight (kg)	79
Unit Dimensions (HWD/in)	5.25 x 17.5 x 28
Unit Dimensions (HWD/cm)	13.3 x 44.5 x 71.1
Material of construction	Black steel cabinet
Form factors supported	3U rack/tower
WARRANTY	
Product Warranty Period	2-year product warranty
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available

Related Items

Extended Warranties		
WEXT3-BP192V12	3-Year Extended Warranty - For BP192V12-3U	Qty: [optional]
WEXT5-BP192V12	5-Year Extended Warranty - For BP192V12-3U	Qty: [optional]

Tower Stands		
2-9U STAND	Tower Stand - Expandable Tower Base Stand UPS Accessory	Qty: [optional]

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3139.